

# JARIFA<sup>2</sup> PRO



| WHEEL<br>SIZE | SIZE/CM | ARTICLE NO.<br>EU/Col.1 | EU/Col.2    |
|---------------|---------|-------------------------|-------------|
| 27,5"         | XS/36   | 628 518 010             | 628 518 150 |
| 27,5"         | S/40    | 628 518 011             | 628 518 151 |
| 29"           | S/40    | 628 518 012             | 628 518 152 |
| 29"           | M/44    | 628 518 013             | 628 518 153 |
| 29"           | L/46    | 628 518 014             | 628 518 154 |
| 29"           | XL/52   | 628 518 015             | 628 518 155 |

- 6061 aluminium, 148x12 mm through axle, internal cable routing, post mount 180 mm
- SR Suntour Raidon RL, 110x15 mm QR, 100 mm travel
- 100 mm
- Bosch Performance CX, 75 Nm, 250 W, 50-300% support power
- BOSCH Powertube, 500 Wh, removeable
- Bosch, 4 Amp
- BOSCH Intuvia
- Shimano Deore XT 8000, 11-speed
- Shimano SLX 7000
- Shimano SLX 11S, 11-46T
- FSA, 18T
- BBB, aluminium, flatbar, 720 mm, rise: 0 mm, backsweep: 9°
- BBB, aluminium, 65 mm
- Acros AZX-212 AH, 1-1/8", tapered, 44/286-ZS56/40
- Sport Saddle
- JD low dropper YSP 15, 31,6 mm, internal
- Shimano Deore M6000, 200 mm / 180 mm
- DT-Swiss H1900, 27,5" 584-30, 29" 622-30, 148x12 mm / 110x15 mm
- Continental X King 2.4
- (1) Sealblue matt,  
(2) Havannabrown matt