

# IZALCO MAX DISC ETAP



WHEEL SIZE	SIZE/CM	ARTICLE NO.	
		EU	UK
28"	XXS/48	628 012 120	628 008 120
28"	XS/50	628 012 121	628 008 121
28"	S/52	628 012 122	628 008 122
28"	M/54	628 012 123	628 008 123
28"	L/56	628 012 124	628 008 124
28"	XL/58	628 012 125	628 008 125
28"	XXL/61	628 012 126	628 008 126

- MAX technology carbon, disc, PF30 BB, 142x12 mm through axle, RAT Evo technology, Di2 ready, flat mount 140 mm, internal brake cable routing
- MAX technology carbon, disc, 100x12 mm RAT through axle, RAT Evo Technology, flat mount 140 mm, internal brake cable routing
- Sram eTap
- Sram Red eTap, 11-speed, short cage
- Sram Red eTap, braze on
- Sram Red eTap HRD
- Sram XG-1190, 11-28T
- Sram Red PF30, 52/36T
- Sram PF30
- front: 52/36, rear: 11-28
- Easton EC90 Aero, carbon, drop: 125 mm, reach: 80 mm
- Easton EA90, aluminium, 31.8 mm, +/- 10°
- 1-1/8", tapered, IS 47/33
- Prologo Scratch STN Rail
- BBB CPX Plus, Carbon, 27.2 mm, 350 mm, set-back: 20 mm
- Sram Red eTap HRD, disc, 160/160 mm
- ZIPP 302, disc center-lock, carbon, 100x12/142x12 mm, 24/24 spokes, 17 mm inner rim width
- Continental GP4000S II, 700 x 25C, Folding
- Racing Green