

JAM² C SL



WHEEL SIZE	SIZE/CM	ARTICLE NO. EU
29"	S/41	628 514 000
29"	M/44	628 514 001
29"	L/47	628 514 002

- ▣ Carbon front triangle, 7005 aluminium rear triangle, 3D forging, 140 mm F.O.L.D. kinematic, 148x12 mm through axle, internal cable routing, post mount 180 mm
- ↘ Fox 34 Factory, 110x15 mm QR, 140 mm travel
- ≡ Fox DPS Factory, 210/55, hardware: shaft25,0x8 mm/body25,0x8 mm, custom tune
- ⚙ 140/140 mm
- ⊙ Shimano Steps E8000, 70 Nm, 250 W
- ⊞ FOCUS T.E.C., 756 Wh, (378 Wh internal, 378 Wh optional external)
- ⊞ FOCUS T.E.C., 4 Amp
- ⊞ SHIMANO Steps E8000, colored LCD display, walk assist, bluetooth
- ⚙ Shimano XTR 9050, Di2, 11-speed
- ⚙ Shimano XTR 9050, Di2
- ⚙ Shimano XTR 11S, 11-40T
- ⊞ FC-E8050-34T Hollow
- ⌒ BBB, aluminium, Di2, flatbar, 760 mm, rise: 0 mm, backsweep: 9°
- ⊞ BBB, aluminium, Di2, 31,8 mm, 55 mm
- ⊞ Acros AZX-212 AH, 1-1/8", tapered, HSZS 44/286-ZS56/40 W
- 🪙 Trail Saddle
- ⚙ Fox Transfer Factory 31,6 mm, internal
- ⚙ Shimano XTR M9020, 200 mm / 180 mm
- ⊞ Race Face Next-R, 662-32, 148x12 mm / 110x15 mm
- ⊞ Continental Trail King SL, 2.4, foldable
- ⊞ Carbon matt/Black